

535,483

Rec'd PCT/PTO 17 MAY 2005

10/535483

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/047181 A1

(51) International Patent Classification⁷: H01L 29/73, 33/00

(21) International Application Number:
PCT/IB2003/004810

(22) International Filing Date: 28 October 2003 (28.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079915.1 20 November 2002 (20.11.2002) EP

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KLOOTWIJK, Johan, H. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SLOTBOOM, Jan, W. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: DUIJVESTIJN, Adrianus, J.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH,

[Continued on next page]

(54) Title: RADIATION-EMITTING SEMICONDUCTOR DEVICE AND METHOD OF MANUFACTURING SUCH A DEVICE



(57) Abstract: The invention relates to a radiation-emitting semiconductor device (10) with a semiconductor body (1) and a substrate (2), wherein the semiconductor body (1) comprises a vertical bipolar transistor with an emitter region (3), a base region (4) and a collector region (5), which regions are each provided with a connection region (6, 7, 8), and the border between the base region (4) and the collector region (5) forms a pn-junction and, in operation, at a reverse bias of the pn-junction or at a sufficiently large collector current, avalanche multiplication of charge carriers occurs whereby radiation is generated in the collector region (5). According to the invention, the collector region (5) has a thickness through which transmission of the generated radiation occurs, and the collector region (5) borders on a free surface of the semiconductor body (1). In this way, less of the generated radiation is lost by absorption and the radiation generated is more readily available to serve as an optical signal for, for example, another part of the device (10) or for another device (10). A second sub-region (5B) in the collector region (5) may be made for example with the aid of a gate electrode (11) with which a conducting channel can be induced in the semiconductor body (1). Preferably, a radiation conductor (14) is present on the surface of the latter. The invention further comprises a method of manufacturing a device (10) according to the invention.

WO 2004/047181 A1